

TEMAX-3
4921220022C



TEMAX-3.4B

- 2 - 2- , 3- 4-
 -
 -
 -
 -
 -
- : IP65

2- ;

• ;

•

Pt100 TEMAX-3 2- Pt100

0,35 TEMAX-3

2 × 15 1,5 2 2 × 10 1,0 2

TEMAX-3

0,35

+1°C + 0,38

(IP65,)

PG9

4 2

240°.

TEMAX-3 4 – 6

Pt100 (2 – 4)

(1)

(1).

- -10 ... 55°C (), - 25 ... 70°C (), - 40 ... 70°C ().

0,2% 10°C

2000 - 50 - 1 /

500 - 50 - 1 /

801-3 (27 ... 1000 , 10)

HSE, DIN 40040

(EMC) EN 50081-1/2 EN 50082-1/2, SS436 1503 (PL4) 255-22-1 (3)


: IP65, 529 EN 60529

: (-) 5

PG9

: 4 ... 10 : 4,0 2

	0 ... 150°C	0 ... 200°C (—)
	Pt100 , 2-			
		15	1,5	² 0,35 , 10 1,0 ² .
()	36	()
		4 ... 20		
	32			
()		
	0,5%	(. . Vs = 2Vpp)		10 ... 400
	0,1%			
	1,0 (1%) ± 0,5°C (–10 ... 15 ... 30 ... 55°C),			688 EN 60688
	0,5°C			
(Vs)	13 ... 36 (DC)	0,1 Vpp	14 ... 36 (DC)	2 Vpp
	5 Vpp			
(RL)				
				$V_s: R_Y = \frac{V_Y - (0,5 V_Y + 13)}{0,02} ()$
	0,1%	13 ... 36 (DC)		0,1 Vpp
	1,0	100%-		2,5
	(0,5%)	



TEMAX-3.3B	0 ... 200°C
------------	-------------



DEIF A/S, Frisenborgvej 33
DK-7800 Skive, Denmark
Tel.: +45 9614 9614, Fax: +45 9614 9615
E-mail: deif@deif.com, URL: www.deif.com

